



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTRON, Inc. All Right Reserved.

SPECIFICATIONS SHEET FOR 1100 SERIES TRUNNION HOLDING FIXTURES

The purpose of this data sheet is to help you to consider all of the features that may be needed or useful in a particular application for a 1100 Series Trunnion-Holding Fixture. It may be helpful to discuss these various features with FLOTRON to determine the cost effectiveness of either the standard or special features. Note that special features will require Engineering and setup charges. Reviewing these considerations should assure you of obtaining the best product at the best price for your particular application.

Definition of part to be handled

Note: See Holding Fixture Overview Table or applicable Data Sheet for standard capacities and sizes.

Part weight: _____

Part Size

Length: _____

Height: _____

Width: _____

Swing radius: _____

Location of center of gravity of part

Distance from CG to trunnion centerline: _____

Distance from CG to mounting plate on gearbox end: _____

Inertia of part: _____



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTRON, Inc. All Right Reserved.

Part mounting height

Standard height is nonadjustable. See applicable holding fixture Data Sheet for standard height.

Standard height: (Specify) _____

Special height: _____ Special adjustable height: _____

Part mounting length

Standard mounting length is adjustable over the length of the Main Beam.

Adjustable distance range: _____

Special fixed distance: _____

Part mounting interface

Standard Mounting Interfaces on the 1100 series include a Mounting Angle or a Mounting Faceplate. See Data Sheets for details.

Standard Mounting Face Plate: _____

Standard Mounting Angle: _____

Special mount: _____ (describe on last page)



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTTRON, Inc. All Right Reserved.

Casters

**1100 series are supplied with 8 swivel casters (with brakes& swivel locks) that are rated in excess of the handler's capacity.
10" Caster wheels have solid urethane treads.**

Standard Casters: _____

Special Casters: which may include any of the following:

Shock absorbing casters: _____ Foam-filled pneumatic tires: _____

Solid cushion rubber tires: _____ Designed for towing: _____

Oversize wheels for rough surfaces: _____

Oversize wheels for soft surfaces: _____

Special size wheels: _____

Materials of Construction

Standard materials are steel, cast iron and aluminum.

Use standard materials: _____

These materials are protected for normal usage. (See finish section).

Use Special materials (specify): _____



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTRON, Inc. All Right Reserved.

Leveling Jacks

Leveling Jacks are a standard option available on 1100 series.

Standard 1100 series Jacks: _____

Special Jacks for 1100 series (specify on last page): _____

Gear Box

Standard ratio is 1124:1 for 1100 series. (Motorized gear ratio is 1975:1).

Standard low backlash gearbox: _____

Special gearbox requirements:

Ratio: _____ Torque: _____

High temperature: _____

Safety Factor

The standard safety factor for 1100 series is 3. This safety factor is based on the yield strength of the materials and includes the maximum capacity load at maximum height, and a .5 G horizontal load.

The standard safety factor: _____

Special Safety factor (specify): _____



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTTRON, Inc. All Right Reserved.

Index Plate

Standard Index plate option is available in increments of 15 degrees.

Standard index plate: _____

Special Index plate requirements: _____

Index increments (degrees): _____ High accuracy _____

Torque: _____ Low backlash: _____ Located at Gearbox end only: _____

Two Index Plates-one at each end: _____

Special Lock Rods to Lock Trunnion Rotation: _____

Finish

Standard finish is textured semi-gloss enamel paint or powdercoat (at manufacturers discretion). Color is blue. Standard plated parts are clear zinc.

Standard finish: _____

Special finishes: _____

High temperature requirements: _____

Color: _____ High gloss, textured, flat? _____

Plating: _____

Clean Room Requirements: _____



2630 Progress Street Vista, CA 92081 USA (ph) 760.727.2700 (fax) 760.727.3957
2010 © FLOTRON, Inc. All Right Reserved.

Miscellaneous Special Options

You may have special requirements not standard on a trunnion holding fixture. FLOTRON can work with you to specify, design and fabricate to your requirements. Your requirements could include but are not limited to any of the following:

Special labeling or warning signs: _____

Special ESD design for electrostatic dissipation: _____

Special size or weight capacity: _____

Special lift eyes: _____

Special provisions for accepting forklifts forks: _____

Special finishes: _____

Other special requirements, describe below: