1100 Holding Fixture

Creating a model number

__ __ __ __ __ - __ __ - __ __ __ - __ __ __ __ __ __ - __ __ __ / __ __ __ - __ __ __ __ - __ __

(blank) - Standard Finish
E- - - - - Ground lug & drag chain for use in EPA's.
C- - - - - Clean Room Finish
N- - - - - Electroless Nickel Plate

Size
1170- 70" Wide frame
1191- 91" Wide frame

Jacks
J0 - - - - Mtg Plates only for Jacks
J2- - - - Jacks with removable crank

Gearbox
(blank) – Standard multiple reduction Gearbox
M - - - - Optional Motorized Gearbox

Index Plate
INDS15 - - - - Standard 15° Index Plate with index stops
INDS"XX" - - Special Index Plate with Index Stops where "XX" = index increments in degrees. (Not available with motorized gearbox option)

Caster
(blank) – Standard Caster with brake & swivel lock

Main Beam
B"XXX" – Main Beam length where "XXX" = length in inches between trunnion interface mounts. (1" increments within the following range)

Model	Min	Max
1170	34"	380"
1191	43"	368"

Trunnion Interface Mounts
P26 - - - - - - - (26" x 21") mounting plate with 8 bolt hole
P26/A40- - - - Standard P26 (1" bolts & 26" x 21" mounting plate) with Standard 40" long angle bolted to P26
P26/A"XX"- - Special angle mount where "XX" = length of angle in inches. (1" increments)

Examples:

1170 - **J2** - **INDS15** - **P26/A40** - **B 120**

70" frame width	Jacks with removable crank	15° Index Plate with stops	Angle Interface 40" length width	Inside Length between Trunnion Mount 120"

1191 - **J0** - **INDS20** - **P26/A50** - **B300**

91" frame width	Mounting Plates only for jacks	20° Index Plate with stops (Special)	Angle Interfaces 50" Length (Special)	Inside Length Between Trunnion Mount 300"

2485 Coral Street Vista, CA 92081 USA (ph.) 760.727.2700 (fax) 760.727.3957
2010 © FLOTRON, Inc. All Rights Reserved.