



SECTION A-A
SCALE 1 : 4

TIPOVER: $23.33 / 45.49 = .51 G$

3. LOAD CAPACITY: 1,000 LBS @ 30° FROM INTERFACE CONSIDERING A SIMULTANEOUS 1.0G VERTICAL & 0.5G HORIZONTAL (WORSE CASE DIRECTION) SIDE LOAD. MAX TORQUE ON GEARBOX = 5,400 IN-LBS (2,000 IN-LBS MAX EASY CRANK TORQUE). SAFETY FACTORS ARE YS = 3 & UTS = 5.

2. FINISHES:

- A. "C" (CLEAN ROOM COMPATIBLE) FINISH- SKY WHITE POWDER COATED END FRAMES, GEARBOX PAINTED GLOSS WHITE EPOXY, NICKEL PLATED COMPONENTS (NO ZINC), STAINLESS STEEL FASTENERS AND MISC. HARDWARE. OPEN-ENDED TUBES NICKEL PLATED. KRYTOX GPL 207 LUBRICANT ON CASTERS & TRUNNION SHAFTS, SYNCO - SUPER LUBE SYNTHETIC GREASE WITH PTFE LUBRICANT ON JACKS (600-800 SERIES), KRYTOX GPL 207 LUBRICANT ON JACKS (900-1200 SERIES).

- B. "N" FINISH - FLOTRON BLUE POWDER COATED FRAMES, GEARBOX PAINTED FLOTRON BLUE, NICKEL PLATED COMPONENTS (NO ZINC), STAINLESS STEEL, OR BLACK OXIDE FASTENERS AND MISC. HARDWARE. STANDARD LUBRICANTS.

- C. STANDARD FLOTRON FINISHES - FLOTRON BLUE POWDER COATED FRAME, GEARBOX PAINTED FLOTRON BLUE, ZINC PLATED STEEL OR BLACK OXIDE FASTENERS, MISC. HARDWARE, AND COMPONENTS. STANDARD LUBRICANTS.

1. WEIGHT IN TITLE BLOCK INCLUDES SIMULATED 1,000 LBS. PAYLOAD.

NOTES:

PROPRIETARY

This Drawing is the property of FLOTRON, Inc. and is not to be used, copied or reproduced in any way other than for the particular purpose for which it is provided, and when said purpose has been fulfilled, it should be destroyed or returned to FLOTRON, Inc.

TOLERANCES UNLESS OTHERWISE SPECIFIED		FRACTION DEC. ANGLES		±.03 ±.010 ±.5°		XX XXX		2630 PROGRESS STREET VISTA, CALIFORNIA 92081 http://www.flotron.com	
APPROVALS		DATE		SCALE		SIZE		DRAWING NO.	
DRAWN DP		3/8/2018		1 : 10		D		8057-500PROP	
CHECKED								REV	
MFG								-	
STATUS		Released		WT: 1901.3 lbmass		Cad software: Inventor		SHEET 1 OF 1	